

Multi-Purpose Accelerometer, Side Exit Connector/Cable, 50 mV/g

Actual Product Size Shown



Product Features

50 mV/g General Purpose Side Exit Sensor


Excellent for Higher g Applications

- ± 100 g, Peak Dynamic Range
- 50 mV/g, $\pm 10\%$ Sensitivity
- 1,0-10000 Hz (60-600,000 CPM)

AC118-1A

2 Pin Connector


Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common



AC118-2C

Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



AC118-3C

Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



AC118-6C

Heavy Duty Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Specifications	Standard	Metric
Part Number	AC118	M/AC118
Sensitivity ($\pm 10\%$)	50 mV/g	
Frequency Response (± 3 dB)	60-600,000 CPM	1,0-10000 Hz
Frequency Response ($\pm 10\%$)	240-360,000 CPM	4,0-6000 Hz
Dynamic Range	± 100 g, peak	
Electrical		
Settling Time	<2 Seconds	
Voltage Source (IEPE)	18-30 VDC	
Constant Current Excitation	2-10 mA	
Spectral Noise @ 10 Hz	8 μ g././Hz	
Spectral Noise @ 100 Hz	2.5 μ g././Hz	
Spectral Noise @ 1000 Hz	1.7 μ g././Hz	
Output Impedance	<100 ohm	
Bias Output Voltage	10-14 VDC	
Case Isolation	>10 ⁹ ohm	

Specifications	Standard	Metric
Environmental		
Temperature Range	-58 to 250°F	-50 to 121°C
Maximum Shock Protection	5,000 g, peak	
Electromagnetic Sensitivity	CE	
Sealing	IP68	
Submersible Depth (AC118-2C/3C)	200 ft.	60 m
Physical		
Sensing Element	PZT Ceramic	
Sensing Structure	Shear Mode	
Weight	5.1 oz	145 grams
Case Material	316L Stainless Steel	
Mounting	1/4-28	
Connector (non-integral)	2 Pin MIL-C-5015	
Resonant Frequency	1,260,000 CPM	21000 Hz
Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt
Calibration Certificate	CA10	

Ordering Information

Standard	AC118-1A (1/4-28 Captive Bolt)	AC118-2C - / (1/4-28 Captive Bolt)	AC118-3C - / (1/4-28 Captive Bolt)	AC118-6C - / (1/4-28 Captive Bolt)
	(length in feet) (termination)	(length in feet) (termination)	(maximum armor length 100 ft.) (cable length in feet) (termination)	(maximum armor length 20 ft.) (cable length in feet) (termination)
Metric	M/AC118-1A (M6x1 Captive Bolt)	M/AC118-2C - / (M6x1 Captive Bolt)	M/AC118-3C - / (M6x1 Captive Bolt)	M/AC118-6C - / (M6x1 Captive Bolt)
	(length in meters) (termination)	(length in meters) (termination)	(maximum armor length 30 m) (cable length in meters) (termination)	(maximum armor length 6 m) (cable length in meters) (termination)

Cable Termination Options: E F L Z



VIBRATION ANALYSIS HARDWARE

INTERTECHNOLOGY INC.

19 Waterman Ave, Toronto, Ont. M4B1Y2
Ph#416-445-5500 Fax#416-445-1170

Toll Free: 1-800-465-1600

Email: sales@intertechnology.com

Website: www.intertechnology.com